

**LAKESIDE SPEEDWAY**  
**2018 SPORT COMPACT RULES**



**1. Body and Frame:**

1. Must remove all glass. Must remove all flammable material except dash (may run sheet metal dash).
2. Windshield must have a minimum of 3 windshield bars in front of driver. Screen is also recommended. Remove all exterior trim, molding, headlights, taillights, lens covers, etc. Trunk lid and front hood latches must be removed and replaced with hood pins only.
3. A 6-point roll cage is mandatory. Cage can be welded to 2"x2" square tubing that is welded/bolted to the rocker panels and the floor (this is only a recommendation). Another possibility would be to weld cage to plates bolted on the floorboard of car. Roll cage tubing must be min. of 1 1/2" by .095 highly recommended 1 3/4" by .095. A minimum of three door bars is required on driver's side. Mounting roll cage to a 4"x4"x11 gauge welded/bolted to the floorboard also acceptable.
4. Racing seats and belts required and must be mounted to roll cage. Must be the same specification as general rules except belts can be a maximum of three (3) years old.
5. Stock or Aluminum bodies are allowed. NO tempered aluminum. You must use an aftermarket nose piece of some type. NO homemade or wedge noses allowed. Body must remain five (5) inches from the ground, this includes skirts also. Body top tin CANNOT have more than two (2) inches of rake/slope on rear tin or trunk area of the body. Interiors must remain open on all cars.
6. Any American or Foreign 4 cylinder passenger car. No four-wheel drive, all-wheel drive, or four wheel steer cars. No Turbochargers or Superchargers.
7. 5/16 tow chain is mandatory on front and back of car. If they are not present and you need towed, you will be disqualified no exceptions.
8. No multi tubed front push type bumpers. Cars with aftermarket noses must use nothing larger than a two (2) inch single tube type bumper. Supports can be used on the top and bottom of aftermarket noses. Any bumper determined to be a battering ram will not be allowed.
9. Stock front bumper. Stock bumper can be reinforced with one 1 3/4" tube inside of stock bumper.
10. Keep sharp edges to a minimum especially at cars corners

**2. Suspension and Steering**

1. All components and mounts must be unaltered, OEM and match year, make/model of car used. Exception is: recommended right rear safety hub (for example 1987-1995 Caravan hub assembly).
2. Brace bar allowed between strut towers in front and rear. No other bracing allowed on front end.
3. No weight jacks, modifications, racing components, aftermarket or homemade traction devices allowed.
4. Rear wheels must track straight ahead and be in alignment with front wheels. No more than 2 degrees camber on any wheel.
5. No center steering. Quick release steering wheel is allowed, must maintain OEM column.
6. No aftermarket remote reservoir power steering.

### **3. Springs/Shocks/Struts**

1. All shocks and struts must remain OEM, in OEM location.
2. OEM springs may be modified.
3. **Maximum one 360 degree by 2" tall spring rubber per wheel.**

### **4. Tires and Wheels:**

1. OEM DOT 13, 14, 15 or 16 inch diameter unaltered passenger tires only. Minimum 60 series, M, N, P, Q, R, S, T, and H speed rated tires only.
2. No racing, mud or snow tires.
3. No re-caps, softening, conditioning, grinding, sanding, siping or grooving allowed.
4. Steel wheels, with standard bead bump and maximum seven inch width.
5. Front tires and wheels must be the same series, size and offset (0.50 inch tolerance); rear tires and wheels must be the same series, size and offset; do not have to match front to rear.
6. Tires must be inside of body.
7. No wheel spacers or bleeder valves.
8. Must use one inch O.D. steel lug nuts on steel wheels.
9. RIGHT FRONT WHEEL MUST HAVE 25lbs OF AIR PRESSURE MINIMUM. Pressure will be checked while in staging. Any car being found with less than 23 pounds in staging will not be allowed to compete and will be disqualified for that race. Lakeside Speedway tire gauge is final.

### **5. Brakes:**

1. Must be steel, unaltered, OEM operative, four wheel disc or drum brakes, and match year, make and model of car use.
2. OEM master cylinder only, in OEM location.
3. No brake shut off or bias adjuster.
4. Steel brake lines only.

### **6. Exhaust**

1. Exhaust manifold must be unaltered, OEM for year, make and model of car used.
2. Smog pump, catalytic converter and air conditioning compressor may be removed.
3. Exhaust must turn toward ground.
4. No exhaust in driver compartment.

### **7. Weight**

1. No ballast (extra weight) of any kind allowed.
2. Any item deemed as ballast will be required to be removed.

### **8. Battery/Starter**

1. One 12 volt battery only.
2. Must be securely mounted with positive terminal covered.
3. Battery must be in Marine type case if mounted in driver compartment.
4. OEM starter only, must be in OEM location.
5. Car must leave initial staging area on demand, unaided, or go to rear of that race.

### **9. Gauges/Electronics**

1. No unapproved cameras, transmitting or listening devices (exception is a one-way Raceiever).
2. 12 volt ignition system only.
3. No ignition boxes.

4. No performance chips.
5. All ignition components must be unaltered, OEM and match year, make and model of car used.
6. Aftermarket analog tach, oil pressure and water temp gauges only.
7. Vehicle computer (ECU) should be mounted in accessible location for inspection.

## **10. Fuel System**

1. Must have complete, unaltered, OEM fuel system for year, make and model of car used. Gasoline only, maximum 93 octane. No E85.
2. No performance additives.
3. Gas tank ahead of rear axle allowed but must install shield under it. Gas tank behind rear axle must be replaced with maximum eight gallon racing fuel cell and relocated to trunk area. Must mount with minimum one inch square tubing or two solid steel straps around entire cell, two inches wide and 0.125 inch thick.
4. Metal firewall or cell cover must be between driver and cell.
5. Fuel cell vent, including cap vent, must have check valve. If racing fuel cell does not have aircraft style positive seal filler neck/cap system - a flapper, spring or ball type filler rollover valve is required.
6. External electric fuel pump wired to the ignition switch allowed with aftermarket fuel cell.
7. No cool cans.
8. Fuel lines through driver compartment must be steel.
9. Aftermarket fresh air pipe and air filter allowed, but no ram air.
10. **Required within easy reach of driver and clearly marked "ON/OFF". A Master On/Off Switch MUST be placed behind the driver seat and clearly marked On and Off. This way all Safety Crews and Officials know when they reach your car where to find the On/Off switch on all cars.**

## **11. Transmission**

1. Must use OEM, unaltered transmission that came in year, make and model of car used.
2. All forward and reverse gears must be operational.
3. Flywheel, flexplate, clutch assembly and torque converter must be unaltered, OEM for year, make and model of car used.
4. No mini clutches or couplers.
5. Must have inspection hole in the bell housing (accessible from top).
6. No transmission coolers in driver compartment.
7. No torque dividing final drive.
8. No locked differentials or CVT transmissions.

## **12. Engine Compartment**

1. Engine and radiator must be OEM, in OEM location for year, make and model of car used.
2. May use solid engine mounts or safety chains.
3. No accumulators/accusumps.

## **13. Engine**

1. 3 or 4 cylinder in-line engines only. Recommended: double overhead cam.
2. All engine components must be unaltered OEM for year, make and model of car used, must match V.I.N.
3. Must use OEM crank, rods, valve sizes, stroke, etc.
4. No aftermarket racing heads.

5. No high performance or sport car engines of any kind.
6. No turbo charged, super charged, rotary engines, or engines utilizing variable cam-timing.
7. No unapproved alterations allowed to any engine. NO aftermarket performance parts. This means keep it stock.

Lakeside is a Fan Friendly, Family Friendly, and Racer Friendly Track. All of us need to respect our sport, fans, families, drivers, owners, pit crew members, engine or chassis builders, track workers, officials, and safety crew.

**Good Luck to All this 2018 Race Season.**

**Director of Competition: Karen Darling – 660-229-0952**

**General Manager: Pete Howey – 913-299-9206**

**SPORT COMPACT PAYOUT**

1. \$120.00
2. \$ 90.00
3. \$ 80.00
4. \$ 70.00
5. \$ 60.00
6. \$ 50.00
7. \$ 40.00
8. \$ 30.00
9. \$ 30.00
10. \$ 30.00
11. \$ 30.00
12. \$ 30.00
13. \$ 30.00
14. \$ 30.00
15. \$ 30.00
16. \$ 30.00
17. \$ 30.00
18. \$ 30.00
19. \$ 30.00
20. \$ 30.00

**TOTAL PURSE: \$990.00**